

3" Thermal Receipt Printer

RETSOL

Retsol RTP-80

- Triple Interfaces: USB, Ethernet & Serial
- Patent Design of Unique Vertical Double Auto Cutter
- Efficient and Stable Printing
- Easy Maintenance
- Supports Windows, Linux OS



Specification

Printer Model	Retsol RTP-80	
Printing	Printing Method Resolution Printing Width Printing Speed Printing Density Printing Direction	Direct thermal line printing Default 203 dpi, 180 dpi can be emulated 72mm(576dots) Max. 230mm/s Adjustable from degree 1 to degree 4 Vertical and horizontal
Interfaces	Built-in USB, RS232, Ethernet	
Auto Cutter	Partial Cut	
Page Mode	YES	
Memory	RAM Flash	2MB 4MB
Character set	Front Number of Columns Alphanumeric Code page	Font A:12*24 Font B:9*17 CHN: 24*24 48/64 95 32
Barcode	1D 2D	UPC-A, UPC-E, EAN8, EAN13, CODE39, ITF, CODEBAR, CODE128, CODE93 QR code, PDF417
Detection	Sensor	Paper out, Cover Open
Power supply	Input Output	AC100V-240V 50-60HZ DC 24V±5%, 2.0A,
Paper	Paper Loading Paper Type Paper Width Paper Thickness Paper Roll Diameter	Front loading Standard Thermal Paper 79.5±0.5mm 0.056~0.13mm 83mm Max.
Reliability	TPH Life Cutter Life Motor Life	150km 1,500,000 times 360,000 hours
Packing Information	Accessories	Power Adaptor, RS232 Cable, CD, Quick Guide, Paper roll
Emulation	ESC/POS	
Driver	Windows(Win10/POSReady/Win8/Win7/Vista/XP/2000), Linux , OPOS	
Certifications	CE/CCC	